





BOEING REALTY CORPORATION FORMER C-6 FACILITY LOS ANGELES, CALIFORNIA

SAMPLING AND ANALYSIS PLAN SUPPLEMENT NO. 2

FORMER CHROMIC ACID TANK LOCATION PARCEL C

To: Mr. Brian Mossman

Boeing Realty Corporation

3760 Kilroy Airport Way, Suite 500

Long Beach, CA 90806

From: Haley & Aldrich, Inc.

Date: February 15, 2001

Re: Sampling and Analysis Supplement No. 2 for the Boeing Realty Corporation Former C-6 Facility

- Parcel C, Former Chromic Acid Tank Location, Los Angeles, California

Haley & Aldrich, Inc. is herein providing this technical memorandum as a supplement to the Sampling and Analysis Plan (dated August 16, 2000), prepared by Kennedy/Jenks Consultants (KJC) for Boeing Realty Corporation's (BRC's) Former C-6 Facility — Parcel C, Los Angeles, California (subject parcel). This technical memorandum describes additional sampling activities to be conducted in proximity to a former chromic acid tank on the subject parcel. The approximate location of the subject former chromic acid tank is depicted on Figure 1.

OVERVIEW/PURPOSE

It is proposed that four soil borings be advanced on the subject parcel. Soil samples will be obtained within the soil borings and will be analyzed to provide additional information regarding total and hexavalent chromium concentrations in soil in proximity to a former chromic acid tank located within former Building 2 on the subject parcel.

PREVIOUS TANK REMOVAL AND REMEDIAL EXCAVATION ACTIVITIES

A former chromic acid tank and two rinse tanks within Building 2 were removed in 1988. The tank removal, remedial excavation, and soil sampling activities are summarized in the following two May 13, 1988 reports prepared by Woodward-Clyde Consultants:

- Chromic Acid Soil Remediation at Douglas Aircraft Company, C6 Facility in Torrance, California
- Recommendations from the Chromic Acid Tank Investigation at the Torrance (C6) Facility, dated 12 May 1988

A review of these reports indicates that chromium-impacted soil was removed following tank removal activities. Impacted soil was excavated based on visual observations of concrete deterioration and field measurements of pH and electrical conductivity (EC); since, soil impacted by chromic acid will

Sampling and Analysis Plan Supplement No. 2 02/16/01

field measurements of pH and electrical conductivity (EC); since, soil impacted by chromic acid will typically have lower pH and higher EC compared to non-impacted soil. These observations and measurements were verified by collecting samples from the excavation and testing them for total chromium. The final limits of the excavation ranged from approximately 10 feet below ground surface (bgs) at the southern end to 20 feet bgs at the northern end. The approximate former tank excavation sample locations (CHROME - 1 through CHROME - 7) are depicted on the attached Figure 2. The total chromium results for these samples ranged from 38 to 170 mg/kg. The field action levels (FALs) for total and hexavalent chromium derived to be health protective and to be within natural background ranges are 40 and 42 mg/kg, respectively. Of the samples collected from the limits of the excavation, two had total chromium results greater than 40 mg/kg. These samples were obtained from a depth of 11 feet bgs at the bottom of the southern portion of the excavation (44 mg/kg at sample CHROME - 1), and a depth of 10 feet bgs along the sidewall of the northern portion of the excavation (170 mg/kg at sample CHROME - 6). The above-referenced May 13, 1988 remediation report further indicates that based on the spatial concentration trends of other samples obtained from the tank excavation, chromium impacted soil likely does not extend more than two feet into the northern sidewall.

FORMER CHROMIC ACID TANK LOCATION

The location of the subject former chromic acid tank and rinse tanks within Building 2 are not apparent based on the tank location description and figures presented in the May 13, 1988 reports. Based information provided by Mr. Scott Lattimore of BRC, it is understood that the former tank was situated at grade (the first floor), and is identified as environmental feature S32 (chromate dip tank) and S31 (Pit) at grid location L30, as depicted on Figure 1 of Technical Memo No. 1, Sampling and Analysis Supplement, dated January 19, 2001.

RECOMMENDED SAMPLING LOCATIONS

The proposed soil boring locations are depicted on the attached Figure 3. As indicated in the attached figure, the borings will be located as follows:

- one boring at the approximate location of sample CHROME 1,
- one boring approximately 5 feet south of former sample CHROME 1,
- one boring at the approximate location of former sample CHROME -6, and
- one boring approximately 5 feet north of former sample CHROME -6.

This area is currently undeveloped. Soil samples will be collected from the two borings to be advanced at and south of former sample CHROME-1 at depths of 11, 15, and 20 feet bgs. Soil samples will be collected from the two borings to be advanced at and north of former sample CHROME-6 from depths 10, 15, 20, and 25 feet bgs.

RECOMMENDED ANALYSIS

Each soil sample will be analyzed for total chromium and hexavalent chromium following U.S. Environmental Protection Agency (EPA) Method 6010B and 7196A, respectively.

Sampling and Analysis Plan Supplement No. 2 02/16/01

INVESTIGATION-DERIVED WASTE (IDW) MANAGEMENT

IDW generated during the course of the investigation will be managed, as noted above, in accordance with the Site-Wide Soil and Waste Management Plan, dated October 31, 2000.

Sincerely yours,

HALLY & ALDRICH, INC.

Richard M. Farson, P.E.

Senior Engineer

Industrial Environmental Group




Scott Zachary

Vice President and Project Manager Industrial Environmental Group

Attachments: Figure 1 – Former Chromic Acid Tank Location Map

Figure 2 – Former Excavation Sample Location Map (Plan View)

Figure 3 – Proposed Boring Location Map



BOE-C6-0107010

BOE-C6-0107011

SOURCE: WOODWARD-CLYDE CONSULTANTS, CHROMIC ACID SOIL REMEDIATION AT DOUGLAS AIRCRAFT COMPANY C-6 FACILITY IN TORRANCE, CALIFORNIA, MAY 13, 1988

PARCEL C

FIGURE 2

FEBRUARY, 2001




FIGURE 3

FEBRUARY, 2001

BOE-C6-0107012